

TRIANGLE MATCHING SYSTEM

Series 900

COLOR MIXING INK SYSTEM

GENERAL DESCRIPTION:

Series 900 plastisol inks are formulated to provide in-house color blending to popular color references. These inks are intermixable and are completely curable. Where matches to fabric colors, or to bright and intense color swatches are required, Fluorescent colors are provided for intermixing. The Color range consists of two systems which are indicated on the accompanying price chart.

STOCK:

Direct prints on knit and woven T-shirts, sweatshirts, jerseys, fleece goods, and bandanna stock.

STENCILS:

All types of solvent resistant emulsions are suitable.

SCREEN MESH:

Monofilament fabrics are recommended. The 900-2 Series is intended for mesh sizes 86T to 196T. The 900-3 Soft Touch version is intended for mesh sizes up to 305T.

CURING:

315° F TO 330° F depending on ink deposit, color and dryer efficiency.

WASH-UP:

Tri-sol 25 or equivalent (Mineral Spirits).

COLOR FORMULAS:

Starting formulas to color references or supplied samples (wet or dry), may be obtained from our Technical Service by telephone or telefax. A Color Formula Guide is also provided in three formats for your convenience : (1.) A simple Compact Formula Book in hard copy of either of the 900-2 or 900-3 series. (2.) An expanded Regular Formula Book that allows the user to pencil in either cost of products or can be used for batch calculation with an external calculator, again in either series. (3.) A complete computer generated program including a manual for use, the ability to add formulas, create and print batch production tickets for various quantities and sizes with automatic calculation of formula components. Both of the matching series formulas are available for use.

This format requires an IBM compatible PC using Windows 95/98 as an operating platform.

Colors outside of the Formulation guide are subject to predictions which will be based on our in-house Color Computer Matching system, especially where it is necessary to have an immediate starting formula.

STORAGE:

These inks must be stored under the same precautions of standard plastisol inks. Exposure to heat above 80° F will be detrimental to ink consistency.

WARNING: FOR INDUSTRIAL USE ONLY KEEP AWAY FROM CHILDREN

NOTE: Please note that all colors are made without the use of lead or heavy metal pigments. The information on this data sheet is based on laboratory tests and production experience. Directions and procedures for use of Triangle-Ink products must be considered as recommendations only. The printer is solely responsible for determining suitability of any Triangle product for a specific application. We recommend that all products be pre-tested prior to production. No warranties are implied or expressed.

Triangle Ink Co., Inc. 53-57 Van Dyke Street, Wallington, New Jersey 07057- (201) 935-2777, (800) 524-1592 – FAX (201) 935-5961